

Pipe Sizes

| Nominal Pipe Size Inches | | Outside Diameter Inches | Schedule | Inside Diameter Inches | Wall Thickness Inches | Weight per ft. lbs. Plain End |
|--------------------------|-----|-------------------------|------------|------------------------|-----------------------|-------------------------------|
| | 1/2 | 0.84 | 5 | 0.71 | 0.065 | 0.538 |
| | | | 10 | 0.674 | 0.083 | 0.671 |
| | | | 40 Std. | 0.622 | 0.109 | 0.851 |
| | | | 80 Ex Hvy | 0.546 | 0.147 | 1.088 |
| | | | 160 | 0.466 | 0.187 | 1.304 |
| | | | 160 XX Hvy | 0.252 | 0.294 | 1.714 |
| | 3/4 | 1.05 | 5 | 0.92 | 0.065 | 0.684 |
| | | | 10 | 0.844 | 0.083 | 0.857 |
| | | | 40 Std. | 0.824 | 0.113 | 1.13 |
| | | | 80 Ex Hvy | 0.742 | 0.154 | 1.474 |
| | | | 160 | 0.614 | 0.216 | 1.937 |
| | | | 160 XX Hvy | 0.434 | 0.308 | 2.441 |
| 1 | | 1.315 | 5 | 1.185 | 0.065 | 0.868 |
| | | | 10 | 1.097 | 0.109 | 1.404 |
| | | | 40 Std. | 1.049 | 0.133 | 1.679 |
| | | | 80 Ex Hvy | 0.957 | 0.179 | 2.172 |
| | | | 160 | 0.815 | 0.25 | 2.844 |
| | | | 160 XX Hvy | 0.599 | 0.358 | 3.659 |
| 1 | 1/4 | 1.66 | 5 | 1.53 | 0.065 | 1.107 |
| | | | 10 | 1.442 | 0.109 | 1.806 |
| | | | 40 Std. | 1.38 | 0.14 | 2.273 |
| | | | 80 Ex Hvy | 1.278 | 0.191 | 2.997 |
| | | | 160 | 1.16 | 0.25 | 3.765 |
| | | | 160 XX Hvy | 0.896 | 0.382 | 5.214 |
| 1 | 1/2 | 1.9 | 5 | 1.77 | 0.065 | 1.274 |
| | | | 10 | 1.682 | 0.109 | 2.085 |
| | | | 40 Std. | 1.61 | 0.145 | 2.718 |
| | | | 80 Ex Hvy | 1.5 | 0.2 | 3.63 |
| | | | 160 | 1.338 | 0.281 | 4.859 |
| | | | 160 XX Hvy | 1.1 | 0.4 | 6.408 |



| Nominal Pipe Size Inches | | Outside Diameter Inches | Schedule | Inside Diameter Inches | Wall Thickness Inches | Weight per ft. lbs. Plain End |
|--------------------------|-----|-------------------------|------------|------------------------|-----------------------|-------------------------------|
| 2 | | 2.375 | 5 | 2.245 | 0.065 | 1.604 |
| | | | 10 | 2.157 | 0.109 | 2.638 |
| | | | 40 Std. | 2.067 | 0.154 | 3.653 |
| | | | 80 Ex Hvy | 1.939 | 0.218 | 5.022 |
| | | | 160 | 1.689 | 0.343 | 7.444 |
| | | | 160 XX Hvy | 1.503 | 0.436 | 9.029 |
| 2 | 1/2 | 2.875 | 5 | 2.709 | 0.083 | 2.475 |
| | | | 10 | 2.635 | 0.12 | 3.531 |
| | | | 40 Std. | 2.469 | 0.203 | 5.793 |
| | | | 80 Ex Hvy | 2.323 | 0.276 | 7.661 |
| | | | 160 | 2.125 | 0.375 | 10.01 |
| | | | 160 XX Hvy | 1.771 | 0.552 | 13.7 |
| 3 | | 3.5 | 5 | 3.334 | 0.083 | 3.029 |
| | | | 10 | 3.26 | 0.12 | 4.332 |
| | | | 40 Std. | 3.068 | 0.216 | 7.596 |
| | | | 80 Ex Hvy | 2.9 | 0.3 | 10.25 |
| | | | 160 | 2.624 | 0.437 | 14.32 |
| | | | 160 XX Hvy | 2.3 | 0.6 | 18.58 |
| 3 | 1/2 | 4 | 5 | 3.834 | 0.083 | 3.472 |
| | | | 10 | 3.76 | 0.12 | 4.973 |
| | | | 40 Std. | 3.548 | 0.226 | 9.109 |
| | | | 80 Ex Hvy | 3.364 | 0.318 | 12.51 |
| 4 | | 4.5 | 5 | 4.334 | 0.083 | 3.915 |
| | | | 10 | 4.26 | 0.12 | 5.613 |
| | | | 40 Std. | 3.826 | 0.237 | 10.79 |
| | | | 80 Ex Hvy | 3.624 | 0.337 | 14.98 |
| | | | 120 | 3.438 | 0.437 | 19.01 |
| | | | 160 | 3.152 | 0.531 | 22.51 |
| 4 | 1/2 | 5 | 40 Std. | 4.29 | 0.247 | 12.53 |
| | | | 80 Ex Hvy | 3.58 | 0.355 | 17.61 |
| | | | 80 XX Hvy | | 0.71 | 32.53 |



| Nominal Pipe Size Inches | Outside Diameter Inches | Schedule | Inside Diameter Inches | Wall Thickness Inches | Weight per ft. lbs. Plain End |
|--------------------------|-------------------------|------------|------------------------|-----------------------|-------------------------------|
| 5 | 5.563 | 5 | 5.345 | 0.109 | 6.349 |
| | | 10 | 5.295 | 0.134 | 7.77 |
| | | 40 Std. | 5.047 | 0.258 | 14.62 |
| | | 80 Ex Hvy | 4.813 | 0.375 | 20.78 |
| | | 120 | 4.563 | 0.5 | 27.04 |
| | | 160 | 4.313 | 0.625 | 32.96 |
| | | 160 XX Hvy | 4.063 | 0.75 | 38.55 |
| 6 | 6.625 | 5 | 6.407 | 0.109 | 7.585 |
| | | 10 | 6.357 | 0.134 | 9.289 |
| | | 40 Std. | 6.065 | 0.28 | 18.97 |
| | | 80 Ex Hvy | 5.761 | 0.432 | 28.57 |
| | | 120 | 5.491 | 0.562 | 36.39 |
| | | 160 | 5.189 | 0.719 | 45.35 |
| | | 160 XX Hvy | 4.897 | 0.864 | 53.16 |
| 7 | 7.625 | Std | 7.023 | 0.301 | 23.57 |
| | | 80 Ex Hvy | 6.625 | 0.5 | 38.05 |
| | | 80 XX Hvy | 5.875 | 0.875 | 63.08 |
| 8 | 8.625 | 5 | 8.407 | 0.109 | 9.914 |
| | | 10 | 8.329 | 0.148 | 13.4 |
| | | 20 | 8.125 | 0.25 | 22.36 |
| | | 40 Std. | 7.981 | 0.322 | 28.55 |
| | | 60 | 7.813 | 0.406 | 35.64 |
| | | 80 Ex Hvy | 7.625 | 0.5 | 43.39 |
| | | 80 XX Hvy | 6.875 | 0.875 | 72.42 |
| | | 160 | 6.813 | 0.906 | 74.69 |

| Nominal Pipe Size Inches | Outside Diameter Inches | Schedule | Inside Diameter Inches | Wall Thickness Inches | Weight per ft. lbs. Plain End |
|--------------------------|-------------------------|-----------|------------------------|-----------------------|-------------------------------|
| | 9.625 | Std | 8.941 | 0.342 | 33.9 |
| | | 80 Ex Hvy | 8.625 | 0.5 | 48.72 |
| 10 | 10.75 | 5 | 10.482 | 0.134 | 15.19 |
| | | 10 | 10.42 | 0.165 | 18.7 |
| | | 30 | 10.136 | 0.307 | 34.24 |
| | | 40 Std. | 10.02 | 0.365 | 40.48 |
| | | Ex Hvy | 9.75 | 0.5 | 54.74 |
| | | 140 | 8.75 | 1 | 104.13 |
| | | 160 | 8.5 | 1.125 | 115.64 |
| 11 | 11.75 | Std | 11 | 0.375 | 45.55 |
| | | Ex Hvy | 10.75 | 0.5 | 60.07 |
| 12 | 12.75 | 5 | 12.42 | 0.165 | 22.18 |
| | | Std | 12 | 0.375 | 49.56 |
| | | 40 | 11.938 | 0.406 | 53.53 |
| | | Ex Hvy | 11.75 | 0.5 | 65.42 |
| | | 160 | 10.126 | 1.312 | 160.27 |
| 14 | 14 | 10 | 13.5 | 0.25 | 36.71 |
| | | 20 | 13.376 | 0.312 | 45.68 |
| | | 30 Std. | 13.25 | 0.375 | 54.57 |
| | | 40 | 13.124 | 0.437 | 63.37 |
| | | Ex Hvy | 13 | 0.5 | 72.09 |
| | | 60 | 12.814 | 0.593 | 84.91 |
| | | 80 | 12.5 | 0.75 | 106.1 |
| | | 100 | 12.126 | 0.937 | 130.7 |
| | | 120 | 11.814 | 1.093 | 150.7 |
| | | 140 | 11.5 | 1.25 | 170.2 |
| | | 160 | 11.188 | 1.406 | 189.1 |



| Nominal Pipe Size (Inches) | Outside Diameter (Inches) | Schedule | Inside Diameter (Inches) | Wall Thickness (Inches) | Weight per ft. lbs. Plain End |
|----------------------------|---------------------------|-----------|--------------------------|-------------------------|-------------------------------|
| 16 | 16 | 10 | 15.5 | 0.25 | 42.05 |
| | | 20 | 15.376 | 0.312 | 52.36 |
| | | 30 Std. | 15.25 | 0.375 | 62.58 |
| | | 40 Ex Hvy | 15 | 0.5 | 82.77 |
| | | 60 | 14.688 | 0.656 | 107.5 |
| | | 80 | 14.314 | 0.843 | 136.5 |
| | | 100 | 13.938 | 1.031 | 164.82 |
| | | 120 | 13.564 | 1.218 | 192.3 |
| | | 140 | 13.124 | 1.437 | 223.5 |
| | | 160 | 12.814 | 1.593 | 245.1 |
| 18 | 18 | 10 | 17.5 | 0.25 | 47.39 |
| | | 20 | 17.376 | 0.312 | 59.03 |
| | | Std | 17.25 | 0.375 | 70.59 |
| | | 30 | 17.124 | 0.437 | 82.06 |
| | | Ex Hvy | 17 | 0.5 | 93.45 |
| | | 40 | 16.876 | 0.562 | 104.8 |
| | | 60 | 16.5 | 0.75 | 138.2 |
| | | 80 | 16.126 | 0.937 | 170.8 |
| | | 100 | 15.688 | 1.156 | 208 |
| | | 120 | 15.25 | 1.375 | 244.1 |
| | | 140 | 14.876 | 1.562 | 274.2 |
| | | 160 | 14.438 | 1.781 | 308.5 |



| Nominal Pipe Size Inches | Outside Diameter Inches | Schedule | Inside Diameter Inches | Wall Thickness Inches | Weight per ft. lbs. Plain End |
|--------------------------|-------------------------|-----------|------------------------|-----------------------|-------------------------------|
| 20 | 20 | 10 | 19.5 | 0.25 | 52.73 |
| | | 20 Std. | 19.25 | 0.375 | 78.6 |
| | | 30 Ex Hvy | 19 | 0.5 | 104.1 |
| | | 40 | 18.814 | 0.593 | 122.9 |
| | | 60 | 18.376 | 0.812 | 166.4 |
| | | 80 | 17.938 | 1.031 | 208.9 |
| | | 100 | 17.438 | 1.281 | 256.1 |
| | | 120 | 17 | 1.5 | 296.4 |
| | | 140 | 16.5 | 1.75 | 341.1 |
| | | 160 | 16.064 | 1.968 | 379 |
| 22 | 22 | 10 | 21.5 | 0.25 | 58.07 |
| | | 20 Std. | 21.25 | 0.375 | 86.61 |
| | | 30 Ex Hvy | 21 | 0.5 | 114.8 |
| | | 60 | 20.25 | 0.875 | 197.4 |
| | | 80 | 19.75 | 1.125 | 250.8 |
| | | 100 | 19.25 | 1.375 | 302.9 |
| | | 120 | 18.75 | 1.625 | 353.6 |
| | | 140 | 18.25 | 1.875 | 403 |
| | | 160 | 17.75 | 2.125 | 451.1 |
| | | 24 | 24 | 10 | 23.5 |
| 20 Std. | 23.25 | | | 0.375 | 94.62 |
| 20 Ex Hvy | 23 | | | 0.5 | 125.5 |
| 30 | 22.876 | | | 0.562 | 140.8 |
| 40 | 22.626 | | | 0.687 | 171.2 |
| 60 | 22.064 | | | 0.968 | 238.1 |
| 80 | 21.564 | | | 1.218 | 296.4 |
| 100 | 20.938 | | | 1.531 | 367.4 |
| 120 | 20.376 | | | 1.812 | 429.4 |